

1. PRODUCT NAME

SIMPLY MODERN

TECHNICAL DATA SHEET

2. MANUFACTURER

Stonepeak Ceramics, Inc.

720 N. Franklin St., Ste 500, Chicago, IL 60654 US

Production Factory:

238 Porcelain Tile Dr., Crossville, TN 38555 US

Telephone: 312.506.2800

Email: <u>info@stonepeakceramics.com</u>
Website: <u>stonepeakceramics.com</u>

3. PRODUCT DESCRIPTION

Simply Modern – is a contemporary collection offering a stunning array of urban tones with a stained concrete appearance. Five colors and three sizes available with corresponding accent pieces and beautiful matte recycled glass mosaic.

Recommended Applications:

Ideally suited for commercial and residential floors and walls.

Finishes/Textures:

- Thru Color
- Honed rectified

Sizes/Thickness:

12" x 24" 1/3" nominal *(8 mm) 12" x 12" 1/3" nominal *(8 mm)

*Denotes work size per ISO 10545-2.

Recommended Grout Joint: 3/32" or greater.

Grout joints of 1/8" inch or less, especially with larger format tiles or running bond patterns, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

For patterns with running bond/brick joints patterns Stonepeak recommends a maximum of 33% offset.

Stonepeak Ceramics Trim System

A variety of bullnose, cove base and mosaic tiles are available for complete design aesthetics.

Refer to Stonepeak Ceramics Product Catalog.

4. TECHNICAL DATA

Physical		land.control	Ctononook
Properties	ASTM Test	Industry Standards	Stonepeak Results
Water		Impervious <	Results
Absorption	C373	0.5 %	≤ 0.1%
Thickness Dimension	C499	Range ± 0.04 Inc. Max	≤ ± 0.04 Inch
Facial Dimension	C499	± 0.25%	≤ ± 0.25%
Warpage Average Diagonal	C485	Range - 0.30% /+ 0.40%	≤ ± 0.40%
Warpage Average edge	C485	Range - 0.30% /+ 0.40%	≤ ± 0.40%
Wedging	C502	± 0.25%	≤ ± 0.25%
Bond Strength	C482	≥ 50 psi	≥ 200 psi
Breaking Strength	C648	≥ 250 lbf	≥ 400 lbf
Hardness (Mohs)	C1895	Range 0 - 10	≥ 7
Visible Abrasion Resistance for Glazed ties	C1027	No Requirement; Range 0 - 5	Class IV
Frost Resistance	C1026	No sample must show alterations to surface	No evidence of Damage
Chemical Resistance	C650	No Requirement; Range E - A	Class A / Unaffected
Stain Resistance	C1378	No Requirement; Range E. A	Class A
DCOF*	ANSI A 326.3	≥ 0.42	≥ 0.55*
Aesthetic Class/Shade Rating	Visual Evaluation Shade & Texture	No Requirement; Range VO - V4	V2

*DCOF: all values given are for matte or honed material. No values are given for polished material. Stonepeak does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

5. INSTALLATION

Surface preparations:

All installation work using Stonepeak Ceramics' tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

All substrates should be between 40 degrees F and 90 degrees F and structurally sound, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds as per ANSI A108.01.

Deflection:

Substrate must conform to all state and local building code requirements and ANSI A108.01 for maximum allowable substrate deflection

Movement joints:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4.and TCNA Details EJ171.

Installation or setting materials:

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.

6. AVAILABILITY AND COST

Stonepeak Simply Modern Collection is available from selected distributors of ceramic tile.

To find accessible information of delivery and product costs for your area, please contact your nearest Stonepeak Ceramics distributor.

See our website the find a distributor near you: http://www.stonepeakceramics.com/serviceswhere to buy.php

7. WARRANTY

Stonepeak Ceramics guarantees that its products will be free of manufacturing defects and they will meet or exceed the performance specifications set forth in ANSI 137.1.

For further information and details please contact your nearest Stonepeak Ceramics Distributor for a written copy of the warranty information.

For distributor information go to our website: http://www.stonepeakceramics.com/serviceswhere to buy.php

8. MAINTENANCE

Care and Maintenance Recommendations Guide.

Please refer to **Stonepeak Ceramics Care and Maintenance Recommendations Guide** for all technical information as to the care of this collection.

9. TECHNICAL SERVICES

Technical Assistance

Guide Specifications, literature, SDS, tile samples, details and installation procedures are all available for your use or libraries.

Please contact your nearest Stonepeak representative for catalogues, physical samples or architectural binders.

Continued Education Programs are available – 1- or 2-hour HSW Learning Units – contact Stonepeak Ceramics' main office to set up a presentation.

10. FILING SYSTEMS

Simply Modern Collection



Simply Crème



Simply Grey



Simply Black



Simply Tan



Simply Coffee

11. ENVIRONMENTAL CERTIFICATIONS

Stonepeak proudly contain factory and product certifications:







12. RECYCLED CONTENT

Products certified by Bureau Veritas. Please ask to see certifications.