

CERAMIC WALL TILE

| UNGLAZED / GLAZED                                               |
|-----------------------------------------------------------------|
| Glazed                                                          |
| THICKNESS                                                       |
| 7.5mm                                                           |
| FINISHES                                                        |
| Glaze   Canvas   Rocky                                          |
| SIZES                                                           |
| 4"x12"                                                          |
| COLORS                                                          |
| Army Black   Army Blue   Army Green  <br>Army Grey   Army White |



| Nominal Size (in) | Actual (in) | Nominal Size (mm) | Actual (mm) | Rectified |
|-------------------|-------------|-------------------|-------------|-----------|
| 4" x 12"          |             | 100 x 300mm       |             | No        |

PERFORMANCE

| PERFORMANCE            |                                                                                     | PROPERTY                     | NORMS                               | STANDARD                          | STONEPEAK<br>RESULT <sup>(1)</sup> |
|------------------------|-------------------------------------------------------------------------------------|------------------------------|-------------------------------------|-----------------------------------|------------------------------------|
| PHYSICAL<br>PROPERTIES |    | WATER ABSORPTION             | ASTM C 373 - 18                     | P4                                | 7.0% < P4 ≤ 20.0 %                 |
|                        |    | BREAKING STRENGTH            | ASTM C 648 - 20                     | ≥ 125 lbf                         | ≥ 125 lbf                          |
|                        |   | VISUAL EVALUATION            | VISUAL VALUATION<br>SHADE & TEXTURE | Range V1 - V4                     | V2                                 |
|                        |  | CRAZING RESISTANCE           | ASTM C424 - 20                      | Pass                              | Pass                               |
| CHEMICAL<br>PROPERTIES |  | THERMAL SHOCK                | ASTM C 484 - 20                     | Pass                              | Pass <sup>(2)</sup>                |
| TECHNICAL<br>FEATURES  |  | THICKNESS VARIATION          | ASTM C 499 - 20                     | 0.031 inch (0.79mm)               | 0.031 inch (0.79mm)                |
|                        |                                                                                     | FACIAL DIMENSION             | ASTM C 1378 - 20                    | ± 0.018 in size < 6"              | ± 0.018 in                         |
|                        | ± 0.30% size ≥ 6"                                                                   |                              |                                     | ± 0.30%                           |                                    |
|                        |  | WARPAGE AVERAGE DIAGONAL     | ASTM C 485 - 16                     | - 0.018 in / + 0.024 in size < 6" | - 0.018/+ 0.024 in                 |
|                        |                                                                                     | WARPAGE AVERAGE EDGE         |                                     | - 0.30% / + 0.40 % size ≥ 6"      | - 0.30% / + 0.40 %                 |
|                        |  |                              |                                     | WEDGING                           | ASTM C 502 - 16                    |
|                        |                                                                                     | - 0.30% / + 0.40 % size ≥ 6" | - 0.30% / + 0.40 %                  |                                   |                                    |
|                        |                                                                                     |                              | ± 0.024 in size < 6"                | ± 0.024 in                        |                                    |
|                        |                                                                                     |                              | ± 0.40 % size ≥ 6"                  | ± 0.40 %                          |                                    |

The material meets compliance with the requirements of America standards ANSI A 137.1: June 2021, ANSI A326.3- 2021 and ASTM Section 15 Volume 15.02.

<sup>(1)</sup> All values given are for textured/natural/structured finish. Values for different finishes are available upon request.

<sup>(2)</sup> Chemical and stain resistance refer to textured/natural finish. For polished/silky finish tests are provided on request. For more detailed information, refer to ANSI A137.1 Specifications for Ceramic Tile.

Product Certifications and Validations



Organizational Memberships

