

CERAMIC WALL TILE

UNGLAZED / GLAZED

Glazed

THICKNESS

8.5mm | 10mm

FINISHES

Natural | Structured

SIZES

16"x48"

COLORS

Domino Limestone Beige | Domino Moon Cream |
Line Beige | Line Black | Line Cream | Line Green |
Line Grey | Line White | Shade Beige | Shade Grey |
Silver Grey | Tide Moon Cream | Full White |
Baycliff Black | Forest Green | Moon Cream |
Limestone Beige | Tide Limestone Beige



Nominal Size (in)	Actual (in)	Nominal Size (mm)	Actual (mm)	Rectified
16" x 48"	15.58" x 47.08"	400 x 1200mm	395.8 x 1195.8mm	Yes

PERFORMANCE

		PROPERTY	NORMS	STANDARD	STONEPEAK ⁽¹⁾ RESULT
PHYSICAL PROPERTIES		WATER ABSORPTION	ASTM C 373 - 18	P4	7% < P4 ≤ 20.0 %
		BREAKING STRENGTH	ASTM C 648 - 20	≥ 125 lbf	≥ 125 lbf
		VISUAL EVALUATION	VISUAL VALUATION SHADE & TEXTURE	Range V1 - V4	V3
		CRAZING RESISTANCE	ASTM C424 - 20	Pass	Pass
CHEMICAL PROPERTIES		THERMAL SHOCK	ASTM C 484 - 20	Pass	Pass ⁽²⁾
TECHNICAL FEATURES		THICKNESS VARIATION	ASTM C 499 - 20	0.031 inch (0.79mm)	0.031 inch (0.79mm)
		FACIAL DIMENSION	ASTM C 1378 - 20	± 0.30% size ≥ 6"	± 0.30%
		WARPAGE AVERAGE DIAGONAL	ASTM C 485 - 16	- 0.30% / + 0.40 % size ≥ 6"	- 0.30% / + 0.40 %
		WARPAGE AVERAGE EDGE		- 0.30% / + 0.40 % size ≥ 6"	- 0.30% / + 0.40 %
		WEDGING	ASTM C 502 - 16	± 0.40 % size ≥ 6"	± 0.40 %

The material meets compliance with the requirements of America standards ANSI A 137.1: June 2021, ANSI A326.3- 2021 and ASTM Section 15 Volume 15.02.

⁽¹⁾ All values given are for textured/natural/structured finish. Values for different finishes are available upon request.

⁽²⁾ Chemical and stain resistance refer to textured/natural finish. For polished/silky finish tests are provided on request. For more detailed information, refer to ANSI A137.1 Specifications for Ceramic Tile.

Product Certifications and Validations



Organizational Memberships

